

Release Date: From 20/04/09

Sharepoint No: NPM00033

NEW

DIN335 3 Flute 90° Countersink

- De-burring
- Countersinking / Counterboring screw holes
- For Countersunk screws acc. to DIN963, 964, 965, 966, 7513, 7516
- For Countersunk screws acc. to ISO 2009, 2010, 7046-1, 7046-2, 7047
- Chamfering of tapping holes
- For use in machine applications


Type N - For non-ferrous, Type UNI - For difficult to machine materials

Benefits

- Constant flute rake along entire cutting face
- Axial and radial adjusted relief
- Higher dimensional precision
- Improved and sharper cutting edge
- Cobalt grade high speed steel

Features

- Chatter-free countersinking and de-burring
- Longer lasting
- Excellent chip flow



AUSTRALIAN MADE AND OWNED SINCE 1917

Catalogue Code				D183	D184			
Discount Group				A1106	A1108			
Material				HSS Co	HSS Co			
Surface Finish				Brt	Futura Nano			
Colour Ring & Application				N	UNI			
Geometry				-	-			
Point Type				90°	90°			
Shank Tolerance				h9	h9			
d ₁	Screw Head	l ₁	d ₂	Pieces	Price	Item #	Price	Item #
4.3	M2	40	4			434889		439198
5.3	M2.5	40	4			436692		439204
6.3	M3	45	5			436708		439211
7.3	M3.5	50	6			436715		439228
8		50	6			436722		439235
8.4	M4	50	6			436739		439242
9.4	M5	50	6			436746		439259
10		50	6			436753		439266
10.4		50	6			436760		439273
11.5	M6	56	8			436777		439280
12.4		56	8			436784		439297
13.4		56	8			436791		439303
15		60	10			436807		439310
16.5	M8	60	10			436814		439327
19	M10	63	10			436821		439334
20.5		63	10			436838		439341
23		67	10			436845		439358
25		67	10			436852		439365
30		71	12			436869		439372
31		71	12			436876		439389
SETS				Contents:				
4 Piece		6.3, 10.4, 16.5, 20.5		4		436890		439402

Product Advice
Countersinks



Sutton Tools